



AC110

Cylinder boring machine

This cylinder boring machine is the result of our long experience and expertise on the market. It ensures the highest level of sturdiness and precision. A cross table guarantees the fast centering between the cylinder and the boring bar.

The spindle speed and the adjustable feed, the automatic control stop and the practical control panel, together with the fast centering and locking of the cylinder and the tool gauging, are the main features of this small well-performing boring machine.

A wide range of devices ensures to easily operate the machine. Browse other cylinder boring machines.

Images may show the product equipped with optional accessories



Standard equipment

Adjustable spindle speed
Adjustable table feed speed
Head power button
Boring depth device with dial indicator
Cross table for quick positioning and centering of cylinder
Precision centering device with dial gauge
Adjustable control stop
Wrench set
Instruction manual

Specifications

Boring capacity: 30 ÷ 125 mm
Boring speed: 100 ÷ 660 RPM
Min-Max distance from head to table: 625 mm
Distance from spindle axis to column: 156 mm
Table surface: 400 x 150 mm
Max longitudinal table travel: 195 mm
Max transverse table travel: 100 mm
Table feed: 1 ÷ 70 mm/min
Spindle motor power: 1.5 kW
Dimensions: 600x350x1600 mm
Weight: 300 kg

Accessories



B03560

Ø 35÷60 mm L = 330 mm boring kit with dial gauge adjustment



B06085

Ø 60÷85 mm L = 320 mm boring kit with dial gauge adjustment



C03560

Ø 35÷60 mm L = 330 mm boring kit with pre-setting system



C06085

Ø 60÷85 mm L = 320 mm boring kit with pre-setting system




AC0090/ACP090

Dial gauge with feeler and clamps



AC0091/ACP091

Dial gauge with micrometer



AC0094/ACP094

Dial gauge with micrometer with magnetic base



TB8512

Dia 85÷125 mm boring equipment



TC8512

Ø 85÷125 mm boring kit with pre-setting system