



# VPT160

## Cylinder head pressure testing machine

---

VPT160 is a hydraulic pressure tester that allows, with precision and ease, detection of possible cracks and leakage of cylinder heads and blocks by immersion in hot water.

The tank, complete with its cover, is manufactured of stainless steel and perfectly insulated to avoid heating dispersion. The water is heated by two powerful heating elements that operate independently and are controlled by an automatic timer which includes heating programs to optimize and reduce the electric usage.

This machine can contain heads and blocks up to 1350 mm of length.

The head is clamped on a cradle actuated by an hydraulic power unit that can move particularly heavy heads and blocks. This cradle also revolves of 360°, allowing the visibility of the whole head, even if when totally submerged, for an easy and prompt detection of leakage.

Contact us for more information, watch the video and download the brochure.

Discover more Cylinder heads equipment

Images may show the product equipped with optional accessories



## Standard equipment

Flat cylinder head support parallels  
Adjustable support parallels for wedge-shaped cylinder heads  
Fixing crossbeams of Plexiglas plate with plates L=380 mm fixing tension rod with nuts and washers  
500x250x30 mm Plexiglas plate  
800x250x30 mm Plexiglas plate  
500x500x8 mm Rubber sheet  
500x500x3 mm Rubber sheet  
Side-locking plate with quick-release coupling  
Standard equipment instruction manual

## Specifications

Maximum cylinder head capacity:  
1350x410x410 mm  
Tank capacity: 580 lt  
Maximum cradle travel: 550 mm  
Heating elements: 2 x 4,5 kW  
Adjustable work temperature: 0 - 90&deg; C  
Cradle rotation speed: 4 rpm  
Cradle up-down speed: 60 mm/sec  
Hydraulic station motor: 0,75 kW  
Cradle gearmotor: 0,25 kW  
Dimensions (LxWxH): 1960x1100x1700 mm  
Weight: 510 Kg