



# RTV530

## Flywheel and clutch pressure plate grinder

---

The RTV530 has been engineered specifically for resurfacing flywheels and clutch friction plates with a maximum diameter of 510 mm (20").

The sturdy structure of some elements, like the base, the column and the rotary table, ensure the maximum level of rigidity and work precision. The clutch pressure plate and flywheel grinder is equipped with an efficient cooling system, complete with a pump and an easy-to-clean settling tank. The complete standard equipment ensures an extremely fast and accurate set-up of the workpieces. Moreover, the RTV530 is suitable for grinding brake discs of cars and trucks for which this kind of machining is required.

Images may show the product equipped with optional accessories




## Standard equipment

Cooling system  
Splash and safety guard  
Taper grindwheel for cast iron  
Grinding wheel dresser  
Wheel dressing diamond  
Set of centering cones  
Set of supporting rings  
Blocking screws  
Wrench set  
Instruction manual


## Specifications

Maximum grinding diameter: 510 mm  
Rotary table diameter: 390 mm  
Maximum distance between - wheel: 175 mm  
Cup grinding wheel diameter: 150 mm  
Table rotation speed: 16 rpm  
Wheel rotation speed: 2800 rpm  
Table motor power: 0.75 kW  
Head motor power: 2.2 kW  
Dimensions (LxWxH): 700x970x1680 mm  
Weight: 380 kg

## Accessories




RTV581  
ø 350 mm Magnetic table



RTV580  
Pressure plate clamping device




RTV591  
Small hole flywheel adapter M12/M16



PV0909

Corner cutting tool for recessed flywheels



PL0CBN

CBN Cup grinding wheel